

TECHNICAL DATA SHEET**Identification of the product and of the company/undertaking****Product identifier**

9190110012	Masking Film Standard, 4m x 150m
9190110013	Masking Film Standard, 5,3m x 150m

Details of the supplier:

Company: Mirka Ltd
Address: Pensalavägen 210
FI-66850 Jeppo, Finland
Phone: +358 20 760 2111
National contact: sales@mirka.com

Product Description

- 9 micron (μ) thick masking film
- High Density Polyethylene Film (PE-HD)
- Electrostatic and treated to ensure fast, easy and complete vehicle masking
- Excellent paint overspray adhesion and no paint flaking

Hazards Identification

No specific danger concerns and no hazard if used for intended application.
This material is not classified as dangerous according to EU directives.

First-Aid Measures

No specific measures need to be taken.

Firefighting measures

Material cannot burn unless preheat and requires a continuous flame source to ignite.
Extinguishing Agents: Water spray, chemical powder, carbonic dioxide.

Storage Conditions

Store under dry conditions and well-ventilated position.
Do not store near sources of heat and keep away from direct sunlight.
Let the material stored in its original packaging and protected against moisture and dust.

Physical and chemical properties

Physical state: Solid (film)
Density: 0,95 gr/cm³

Toxicological information

No irritant effects. Not sensitising effect known.
Not Toxic and/ or harmful effects are expected in case of skin contact.





Reference / Product name:
Masking Film Standard

Version/Revision (date): 2/24.03.2022
page 2 of 2

Ecological information:

- This material is 100% recyclable
- The material is not considered hazardous waste;
scrap materials may be disposed of at approved landfills or preferably by incineration in
accordance with existing international, EU Community, national and local regulations
- All disposal methods must be in compliance with the EU framework directive 91/156/EEC.

Transport information

According to national and international guidelines, which regulate the road-, rail-, air-, and sea transport,
this product is classified as not dangerous.

Shelf Life

7-10 months

Custom Tariff number

3920-10

